Collomix

Rotary mixer **AOX-S**Lump free and quickly mixed



45.499



■ For mixing volumes of up to 40 litres ready-mix; suitable for mortar, sreed, plaster, tile adhesives, etc. (mixing tool KR); Thin-bed mortar, self-leveling compound, Pointing mortar, etc. (Mixing tool DLX)

high-speed mixing tool for lump free intermixing

Mixing action via rotating tub

Edge and bottom scraper

Safety cut-off

compact and mobile

2 interchangeable mixing tools (KR & DLX)

Technical data AOX-S			
Size of mixing tub:	65 Ltr.		
Max. effective volume:	max. 40 litres		
Power rating of mixing mechanism:	1,0 kW / 230		
RPM of mixing mechanism:	750 min ⁻¹		
RPM of tube drive:	18 min ⁻¹		
Dimensions (I x w x h):	60x82x87		
Weight:	51 ka		

Consistency range: very stiff to plastic				
Material (weight without added water):	DLX	KR		
Slightly moist concrete with grain size of -8 mm (30 I)	-	+		
Concrete with max. grain size of 8 mm (30 l)	-	+		
Cement screed (35 I)	-	+		
Universal mortar (40 l)	-	+		
Gypsum-lime mortar (35 l)	-	+		
Light wall mortar (25 l)	-	+		
Cement stucco (40 I)	+	+		
Gypsum plaster (40 l)	+	+		
Loam plaster without fiber (40 l)	+	+		
Heat-insulating plaster (30 l)	-	+		
Mortar for natural stone slabs (30 l)	-	+		
2-component slab pointing mortar (-1,2 mm, 30 l)	+	+		
Middle-bed mortar (25 l)	-	+		
Tile adhesives (flexible mortar, 25 l)	-	+		
Pointing mortar (25 I)	+	+		
Consistency range: soft to spreading				
Pouring screed (40 I)	+	+		
Soft/spreading types of mortar (40 l)	+	+		
Thin-bed mortar, cement for concrete precision blocks (30 l)	+	+		
Creamy types of plaster (40 l)	+	+		
Adhesive grouting compounds as backing for plaster (30 l)	+	+		
Tile adhesives (25 l)	+	+		
Pointing mortar (25 l)	+	+		
Joint cements (30 I)	+	+		
Adhesive grouting compounds as backing for panels/tiles (30 l)	+	+		
2-component sealing grouting compounds (25 l)	+	+		
Leveling compounds (25 I)	+	+		
2-component epoxy-resin and sand mix (30 l)	+	+		
+ = suitable	- = un	suitable		





RIGHT PRODUCT **RIGHT** PRICE **RIGHT** TO YOUR SITE 09 42 68 101 <u>sales@everitts.co.nz</u> <u>www.everitts.co.nz</u>