



FormOil DF

THE SAFER CHOICE

EZEE FormOil DF is a Diesel-Free Chemically Active Form Release Agent specially engineered to positively prevent bonding of the concrete to forms and form liners.

- ✓ Improves release of formwork.
- ✓ Protects formwork against rust.
- ✓ Reduces cleaning of formwork.
- ✓ Reduces concrete buildup on formwork and liners.
- ✓ Leaves no residue, stain or discoloration.
- ✓ Helps reduce dusting of concrete.

USES:

EZEE FormOil DF is effective on concrete construction moulds and formwork. EZEE FormOil DF is not suitable for tilt slab construction work.

COVERAGE:

Spray application of EZEE FormOil DF is recommended with coverage as follows:

Steel, Plastic, Fiberglass:	50 m ² per litre
Conditioned Aluminum:	50 m ² per litre
HDO Plywood:	50 m ² per litre
MDO Plywood:	35 m ² per litre
Dimensional Timber:	25 m ² per litre
BB Grade Plywood:	25 m ² per litre

APPLICATION:

Ready to use. Do not dilute. Form surfaces should be clean of dirt, rust, scale and concrete build up prior to application. EZEE FormOil DF should be spray applied using a misting spray tip so that application is in a thin uniform film to maximize product performance and economy. Over application will not produce better results and may cause dusting.

Excess material or puddles should be removed with a squeegee and absorbent rags.

When properly applied, EZEE FormOil DF will not leave any residue or stain on the concrete, producing a smooth, architectural concrete surface ready for subsequent coatings. Coating manufacturer's recommendations for surface preparations must be followed.

Sprays easily in cold temperatures. Proper application substantially reduces concrete surfaces voids and extends the life of wood forms.

TECHNICAL DATA

EZEE FormOil DF meets V.O.C. emission requirements for form releases (EPA limit <450 g/L).

V.O.C. CONTENT:	<250 g/L
COLOUR:	Amber
SPECIFIC GRAVITY:	Approx 0.89 kg/Litre
FLASHPOINT:	>200°F (93°C)

FIRST AID & PRECAUTIONS:

Skin Contact: Wash skin thoroughly with soap and water after handling. Seek medical attention if irritation develops and persists.

Inhalation: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.

Ingestion: If product is swallowed, call POISON CENTRE or doctor immediately. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. If medical advice is needed: Have product container or label at hand.

Medical Conditions Generally Aggravated By Exposure: Pre-existing skin, respiratory system or eye problems may be aggravated by prolonged contact.

Symptoms and Effects Both Acute and Delayed: Exposure to skin may cause irritation.

Recommendations to Physicians: Treat symptoms and eliminate overexposure.

Do not use until all safety precautions have been read and understood. If exposed or concerned: Get medical advice/attention. Refer Product Safety Data Sheet for details.

Limitations: EZEE FormOil DF should not be used as a bond breaker in tilt up construction.

Warning: Do not expose to or apply near fire or flames. For well ventilated or exterior use only.

Precautions: Do not cut or weld container. Keep away from open flame. Industrial use only.

Disposal: Recover and recycle if possible. Clean empty container thoroughly, wash with detergent and water. Do not reuse packaging for any other purpose other than to refill with original material. Waste material can be disposed of by incineration (preferably at high temperature) by an approved agent according to local regulations. Dispose of in accordance with local rules.

Supplied by Everitt Site Supplies Ltd. Everitt Site Supplies Ltd provides the above information in good faith and without warranty. The data represents typical values which can be updated at any time, and this information supersedes previous issues. No liabilities can be accepted for any damage or loss arising from the use of Everitt Site Supplies Ltd literature or its products, because Everitt Site Supplies Ltd has no continuous control on how the materials are mixed, placed or cured.

Manufactured by SpecChem, 1511 Baltimore Ave, Kansas City, MO 64108, USA.

24 hour emergency contact number:
0800 POISON / 0800 764766

Material Safety Data Sheet



Supplied by



Making your job easier!

09 42 68 101

sales@everitts.co.nz

www.everitts.co.nz